

Datasheet Overspeed Governor



Installation in machinery room **EN81-1/2:1998+A3:2009**

Inquiry **Order**

Date: _____

Please tick as appropriate

Invoice address:		Deliver address:	
Name.:			
Company:		Company:	
Street:		Street:	
Zip-Code;City		Zip-Code; City	

Email:	Phone:	Fax:
--------	--------	------

Typ:

- Typ 8 ASV rope distance 200mm NL 10-400-1002-131-02**
Va = 0,50 – 1,50 m/s
Vn max. 1,25 m/s
 - Anti-Creep Protection 12V 24V
- Typ 7 ASV rope distance 300mm NL 10-400-1002-131-01**
Va = 0,70 – 3,43 m/s
Vn max. 2,98 m/s
 - Anti-Creep Protection 12V 24V
- Typ 9 ASV rope distance 300mm NL 10-400-1002-131-03**
Va = 0,50 – 0,80 m/s
Vn max. 0,69 m/s
 - Anti-Creep Protection 12V 24V

The Anti-Creep Protection can also be used as a remote release!

Key numbers:

Quantity:	<input style="width: 50px;" type="text"/>	Nominal speed Vn:	<input style="width: 100px;" type="text"/>
		Tripping speed Va:	<input style="width: 100px;" type="text"/>

With:

- hardened rope groove for upwards catching
- test groove

Attachments to governor:

- Safety switch 2240 pre cut-off , electromagnetic resettable (when Vn > 1,0m/s):
- Safety switch 1475 electromagnetic resettable (when Vn < 1,0m/s):
- Add-on kit for rotary pulse encoder: 1:2 1:4
- Cover for governor:

Tension weight to be mounted to the rail:

- Typ SRV Downwards catching (tension weight 15kg):
- Typ SR/FO-V downwards and upwards catching (tension weight 30kg):
- Typ SGI-S downwards and upwards catching with intergrated diverter pulley:
(tension weight 65kg)

Tension weight to be mounted to the pit floor for catching in bidirectional flow:

- Typ SGI with intergrated diverter pulley and 65kg tension weight:
- Typ SGD Tension weight with side load direction for support of governor or deflection sheave (tension weight 75kg)

Supports:

- Support with auxiliary current emergency limit switch:
- timbers
- switch springs

Additional switches:

- Auxiliary current emergency limit switch on:
- Direction dependent switch (for releasing an additional brake):
- Safety switch with double contact: (for releasing an additional brake)

OSG <input type="checkbox"/>		SGD <input type="checkbox"/>
detent <input type="checkbox"/>	Not detent <input type="checkbox"/>	Only detent <input type="checkbox"/>
detent <input type="checkbox"/>	Not detent <input type="checkbox"/>	Only detent <input type="checkbox"/>

Remarks / desired date:

Our certificate and instruction manuals can be download from our homepage www.bode-components.com