

Datasheet Overspeed Governor

Installation in machinery room EN81 / AGB



Inquiry Order

Date: _____

Please tick as appropriate

Invoice address:		Deliver address:	
Name.:			
Company:		Company:	
Street:		Street:	
Zip-Code;City		Zip-Code; City	

Email:	Phone:	Fax:
--------	--------	------

Typ:

- | | |
|---|---|
| <input type="checkbox"/> Typ 8 rope distance 200mm AGB 069/2 | Va = 0,50 – 1,50 m/s
Vn max. 1,25 m/s |
| <input type="checkbox"/> Typ 7 rope distance 300mm AGB 068/2 | Va = 0,70 – 3,43 m/s
Vn max. 2,98 m/s |
| <input type="checkbox"/> Typ 9 rope distance 300mm AGB 084/1 | Va = 0,50 – 0,80 m/s
Vn max. 0,69 m/s |

Key numbers:

Quantity: Nominal speed Vn:
 Tripping speed Va:

With:

- hardened rope groove for upwards catching
 test groove

Attachments to governor:

Remote release:	230V	<input type="checkbox"/>	110V	<input type="checkbox"/>
Anti-Creep Protection (can also be used as remote release):	12V	<input type="checkbox"/>	24V	<input type="checkbox"/>
Safety switch 2240 pre cut-off , electromagnetic resettable (when Vn > 1,0m/s):		<input type="checkbox"/>		
Safety switch 1475 electromagnetic resettable (when Vn < 1,0m/s):		<input type="checkbox"/>		
Add-on kit for rotary pulse encoder:	1:2	<input type="checkbox"/>	1:4	<input type="checkbox"/>
Cover for governor:		<input type="checkbox"/>		

Tension weight to be mounted to the rail:

Typ SRV	Downwards catching (tension weight 15kg):	<input type="checkbox"/>
Typ SR/FO-V	downwards and upwards catching (tension weight 30kg):	<input type="checkbox"/>
Typ SGI-S	downwards and upwards catching with integrated diverter pulley: (tension weight 65kg)	<input type="checkbox"/>

Tension weight to be mounted to the pit floor for catching in bidirectional flow:

Typ SGI	with integrated diverter pulley and 65kg tension weight:	<input type="checkbox"/>
Typ SGD	Tension weight with side load direction for support of governor or deflection sheave (tension weight 75kg)	<input type="checkbox"/>

Supports:

Support with auxiliary current emergency limit switch:
 timbers
 switch springs

Additional switches:

Auxiliary current emergency limit switch on:
 Direction dependent switch (for releasing an additional brake):
 Safety switch with double contact:
 (for releasing an additional brake)

OSG <input type="checkbox"/>		SGD <input type="checkbox"/>
detent <input type="checkbox"/>	Not detent <input type="checkbox"/>	Only detent <input type="checkbox"/>
detent <input type="checkbox"/>	Not detent <input type="checkbox"/>	Only detent <input type="checkbox"/>

Remarks / desired date:

Our certificate and instruction manuals can be download from our homepage www.bode-components.com