

Enquiry & Order Form

Tension weights / Substructure

Version 25-6



Your Ref.:

Quantity:

Delivery date:

Date:

☐ Enquiry

☐ Order

Invoice address:		Delivery address (if different):
Company:		
Street:		
Zip code/ City:		

Tension weights for installation on the guiding rail:

(Incl. slack rope switch and cover according to EN 81)

- | | | | |
|----------------------------------|---|---|--------------------------|
| Type SRV
(Picture No. 1) | 200mm <input type="checkbox"/> 300mm <input type="checkbox"/> | catch in downwards direction incl. 15kg weight: | <input type="checkbox"/> |
| Type SR/FO-V*
(Picture No. 2) | 200mm <input type="checkbox"/> 300mm <input type="checkbox"/> | catch in up- and downwards direction incl. 30kg weight: | <input type="checkbox"/> |
| Type SGI-S*
(Picture No. 3) | 200mm <input type="checkbox"/> 300mm <input type="checkbox"/> | catch in up- und downwards direction incl. integrated pulley and 65kg weight:
(without cover because of integrated pulley) | <input type="checkbox"/> |

Tension weights for installation on the bottom of the shaft for catching in up- and downward direction:

(incl. slack rope switch according to EN 81)

- | | | | |
|------------------------------|---|--|--------------------------|
| Type SGI*
(Picture No. 4) | 200mm <input type="checkbox"/> 300mm <input type="checkbox"/> | incl. integrated pulley and 65kg weight: | <input type="checkbox"/> |
| Type SGD*
(Picture No. 5) | | as duplex guiding stand incl. pulley with bearing stand and 75kg weight: | <input type="checkbox"/> |

Substructure with auxiliary emergency switch and spiral springs

- | | | |
|--|---------|--------------------------|
| Substructure 300mm Type 7 up to VA 1,49m/s | 500mm | <input type="checkbox"/> |
| Substructure 300mm Type 7 from VA 1,50m/s | 1500mm* | <input type="checkbox"/> |
| Substructure 200mm Type 8 up to VA 1,50m/s | 500mm | <input type="checkbox"/> |



SRV (15 kg)
(Picture No. 1)



SRFO* (30 kg)
(Picture No. 2)



SGI-S* (65 kg)
(Picture No. 3)



SGI* (65 kg)
(Picture No. 4)



SGD* (75 kg)
(Picture No. 5)

* The delivery of these tension weights and substructures is possible only on a pallet with a freight carrier.