

6.0**ORDER data sheet****Tension weights / Substructure**

Version 19-01

BODE
COMPONENTS

Order No. _____

Date: _____

Delivery date: _____

Quantity: _____

Invoice address:		Delivery address (if different)
Company:		
Street:		
Zip code/ City:		

Tension weights for installation on the guiding rail:

(Incl. slack rope switch and cover according to EN 81)

- | | | | | |
|---------------|--------------------------------|--------------------------------|---|--------------------------|
| Type SRV | 200mm <input type="checkbox"/> | 300mm <input type="checkbox"/> | catch in downwards direction incl. 15kg weight: | <input type="checkbox"/> |
| Type SR/FO-V* | 200mm <input type="checkbox"/> | 300mm <input type="checkbox"/> | catch in up- and downwards direction incl. 30kg weight: | <input type="checkbox"/> |
| Type SGI-S* | 200mm <input type="checkbox"/> | 300mm <input type="checkbox"/> | catch in up- und downwards direction incl. integrated pulley and 65kg weight:
(without cover because of integrated pulley) | <input type="checkbox"/> |

Tension weights for installation on the bottom of the shaft for catching in up- and downward direction:

(incl. slack rope switch according to EN 81)

- | | | | | |
|-----------|--------------------------------|--------------------------------|--|--------------------------|
| Type SGI* | 200mm <input type="checkbox"/> | 300mm <input type="checkbox"/> | incl. integrated pulley and 65kg weight: | <input type="checkbox"/> |
| Type SGD* | | | as duplex guiding stand incl. pulley with bearing stand and 75kg weight: | <input type="checkbox"/> |

Substructure with auxiliary emergency switch and spiral springs

- | | | |
|--|---------|--------------------------|
| Substructure 300mm Type 7 up to VA 1,49m/s | 500mm | <input type="checkbox"/> |
| Substructure 300mm Type 7 from VA 1,50m/s | 1500mm* | <input type="checkbox"/> |
| Substructure 200mm Type 8 up to VA 1,50m/s | 500mm | <input type="checkbox"/> |

* The delivery of these tension weights and substructures is possible only on a pallet with a freight carrier.