

<b>DELIVERY LINE</b>		
<b>Spare parts for Overspeed Governor</b>		
<b>8.0</b>	from 01st January 2019	
	Version 19-01	



## 8.1 Safety switches

Description	Order No.
Safety switch with double contact 2NOC, without locking device To release of an addition brake	521562
Safety switch till 1,49 m/s tripping speed (Va) 1NOC, 1NCC Without locking device <b>(Standard)</b>	521563
Safety switch till 1,49 m/s tripping speed (Va) 1NOC, 1NCC with locking device	521564
Safety switch till 1,49 m/s tripping speed (Va) with 2NCC and with locking device	522500
Resettable pre-cutoff (electromagnetic) switch 2NCC, 1NOC till 1,49 m/s tripping speed (Va)	521475
Resettable pre-cutoff (electromagnetic ) switch 1NCC from 1,50 m/s tripping speed (Va) <b>(Delivery possible only mounted on the governor)</b> <b>(Standard)</b>	422230
Resettable pre-cutoff (electromagnetic ) switch 2NCC, 1NOC from 1,50 m/s tripping speed (Va) <b>(Delivery possible only mounted on the governor)</b>	422240
Switch plate for switching depending on direction.	580151

## 8.2 Covers

According to EN81	Order No.
Cover for overspeed governor type 7/9	580017
Cover for overspeed governor type 8	580018

According to Industrial Safety Regulation	Order No.
Cover for overspeed governor type 7/9	590201K
Cover for overspeed governor type 8	590200K
Cover for overspeed governor type 7/9 with cut for anti creep protection or remote release	590203K
Cover for overspeed governor type 8 with cut for anti creep protection or remote release	590202K

## 8.3 Rope and accessories

Description	Order No.
Rope 6,5 mm galvanized	590140
Rope lock incl. wedge, DIN 15315	590143
Wire rope clips	590144

## 8.4 Substructures

Description	Order No.
Suited for governor type 7/9 300 mm: - substructure incl. auxiliary current-final limiting switch and spiral spring till 1,49 m/s tripping speed (Va)	580035
- substructure incl. auxiliary current-final limiting switch and spiral spring from 1,50m/s tripping speed (Va)	580036
Suited for governor type 8 200 mm: - substructure incl. auxiliary current-final limiting switch and spiral spring till 1,50m tripping speed (Va)	580037

## 8.5 Governor mounting on the guiding rail

Description	Order No.
Bracket for rail mounting of the overspeed governor	580550

## 8.6 Deflection shaves

Description	Order No.
Deflection sheave incl. bearing bracket for mounting in the pit floor (incl. rope cover according to EN81)	
- with 300 mm deflection sheave	580051
- with 200 mm deflection sheave	580052

## 8.7 Various parts

Description	Order No.
Adapter plate Type 7 / 9	580062
Adapter plate Type 8	580063
Pendulum roll	590104