

## DELIVERY LINE tension weights



6.0

from 01st January 2019

Version 19-01

### 6.1 Tension weight system: catch in downwards direction

Description	Order No.
Tension weight for installation on the guiding rail <b>SRV</b>	
- Tension weight 15kg 200 mm incl. fastening for rail, slack rope switch 621575 and cover according to EN 81	680162
- Tension weight 15kg 300 mm incl. fastening for rail, slack rope switch 621575 and cover according to EN 81	680163

### 6.2 Tension weight system: catch in upwards- and downwards direction

Description	Order No
Tension weight for installation on the guiding rail <b>SR/FO-V</b>	
- Tension weight 30kg 200 mm incl. sliding bracket, slack rope switch 621575 and cover according to EN 81	680161V
- Tension weight 30kg 300 mm incl. sliding bracket, slack rope switch 621575 and cover according to EN 81	680160V
Tension weight with vertical guide for installation on the guiding rail <b>SGI-S</b>	
- Guiding stand with integrated tension pulley 200mm, with tension weight 65kg and slack rope switch 621565 according to EN81	680270
- Guiding stand with integrated tension pulley 300mm, with tension weight 65kg and slack rope switch 621565 according to EN81	680271
Tension weight with vertical guide <b>SGI</b>	
- Guiding stand with integrated tension pulley 200mm, with tension weight 65kg and slack rope switch 621565 according to EN81	680170
- Guiding stand with integrated tension pulley 300mm, with tension weight 65kg and slack rope switch 621565 according to EN81	680171

The examination certificate for tension weights is issued by Liftinstituut B.V.

### 6.3 Slack rope switch for tension weight

Description	Order No.
Slack rope switch for tension weight SGI and SGI-S 65kg according to EN 81	621565
Slack rope switch for tension weight SRV and SR/FO-V according to EN 81	621575
Slack rope switch for the duplex guiding stand according to EN 81	521564

### 6.4 Governor in the pit floor

Description	Order No.
Duplex guiding stand for installation of the overspeed governors in the pit floor, incl. weight 75kg, slack rope switch 1564 according to EN 81	680040
Covering for installation in the pit floor:	
- for tension pulley 200mm	680127
- for tension pulley 300mm	680128

The examination certificate for tension weights is issued by Liftinstituut B.V.